

# **FA-H20**

# **FLOOR DOOR H20 loading**

### **Application**

 Indoor or Outdoor applications where dirt and water are prevented from falling into work area. Drainage is provided through threaded coupling in channel

#### **Product Features**

- Angle frame construction with integral anchor flange is designed to be
- Diamond plate door panel is equipped with a flush aluminum drop handle and an automatic hold open arm, along with stainless steel compression spring & stainless steel slamlock
- Designed for off-street locations that may occasionally receive AASHTO H 20-44 wheel loads



Double Leaf

## FA-H20 Floor Door Specifications:

Material: Aluminum door and frame; stainless steel hinges and hardware **Door:** 1/4" aluminum diamond plate reinforced to meet AASHTO specification H 20-44 for traffic loading (16000 lb. wheel load over 10" x 20" area with 30% added for impact)

**Hinge:** Stainless steel butt hinges with tamperproof stainless steel bolts and nuts

Frame: Angle frame fabricated from aluminum extrusion with an integral 1" anchor flange Opening Device: Automatic hold open arm with red vinyl grip allows door panel to open to 90 degrees, locking door in open position, and allowing for easy control when closing door panel. Stainless steel compression springs provide lift assistance. Available with electrical actuators, operated by wall mounted push button switch, and remote control

Standard Latch: Flush aluminum drop handle, stainless steel slamlock with a fixed inside handle, removable outside handle, and removable threaded plug


Finish: Mill finish, with bituminous coating on exterior of frame

#### FA-H20 STANDARD SIZES

\*Double Leaf

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
24 x 24	610 x 610	62	28
24 x 30	610 x 762	65	30
24 x 36	610 x 914	87	39
30 x 30	762 x 762	86	39
30 x 48	762 x 1219	133	60
36 x 36	914 x 914	122	55
36 x 48	914 x 1219	150	68
42 x 42	1067 x 1067	170	77
48 x 48*	1219 x 1219	221	100
48 x 72*	1219 x 1829	330	150
60 x 60*	1524 x 1524	399	181



U.S.A.: info@acudor.com / 800.722.0501 MEXICO: infomx@acudor.com / +521 (844) 101-0081

For detailed specifications see submittal sheet

CANADA: info@acudor.ca / 844.228.3671 INDIA / MIDDLE EAST / NORTH AFRICA: ap-imea@acudor.com / +971-4-399-6966

INTERNATIONAL: info@acudorintl.com / 905.428.2240 SITE: www.acudor.com