

WD-8000

DUCT & SPECIALTY DOORS Walk Through Door

Application

- Designed to provide convenient walk through access to duct work interiors & air handling units
- Low to medium pressure systems and plenums

Product Features

- Heavy duty construction, along with a continuous hinge and compression handles
- Optional Features: Removable Door Panel / Vision Panel / High Pressure Units / Key Operated Handles

WD-8000 Access Door Specifications:

Material: Galvanized steel, also available in Aluminum and Stainless Steel

Door: 22 gauge

Mounting Frame: Double panel frame is 1 15/16" wide x 1 1/2" deep extruded aluminum with mitred corners

Gasket: 1/8" thick x 1/2" wide closed cell neoprene gasketing between door and frame

Hinge: Continuous steel piano hinge—opens 180 degrees

Insulation: Door panel filled with 1" thick fiberglass insulation - 4 R value

Standard Latch: Dual acting compression handles—operable from both sides

Units 48" high and under to have 2 handles

Units over 48" high to have 3 handles

Finish: Mill finish



WD-8000 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
24 x 36	610 x 914	52.8	24
24 x 48	610 x 1219	77.0	35
24 x 60	610 x 1524	97.0	44
24 x 72	610 x 1829	114.4	52
30 x 36	762 x 914	70.4	32
30 x 48	762 x 1219	95.0	43
30 x 60	762 x 1524	119.0	54
30 x 72	762 x 1829	143.0	65

Wall opening is normal door size plus +3/8" (9mm)
For detailed specifications see submittal sheet

