





SECTION A–A

SPECIFICATIONS

1. 1/4" X 3" X 3" STEEL ANGLE FRAME
2. 1/4" STEEL DIAMOND PLATE COVER.
3. TORSION/CAM OPERATING MECHANISM
4. STANDARD SLAM LOCK
5. REMOVABLE SQUARE KEY WRENCH
6. BILCO AUTOMATIC HOLD OPEN ARM W/ RED VINYL GRIP
7. 3/8" DIA. STEEL ACHOR STRAP.
8. 3/8" X 3/4" STEEL COVER SUPPORT BAR. (3 SIDES)
9. STEEL CAST HINGES
10. GUARD CHAIN
11. 1/4" X 1 1/4" ASTRAGAL
12. GUIDE ARM (IF REQ'D)

SHOP FINISH:
STEEL: RED OXIDE PRIMER
HARDWARE: ZINC PLATED/CHROMATE SEALED
(UNLESS OTHERWISE SPECIFIED)

REINFORCED FOR 300 Lbs. PER Sq. Ft.
(1465 kg. PER Sq. METER) LIVE LOAD

INSTALLER NOTES:

A. USE CAUTION. COVER IS SPRING LOADED. DO NOT REMOVE SAFETY SHIPPING BOLT UNTIL UNIT IS TO BE INSTALLED AND IN NORMAL HORIZONTAL OPERATING POSITION.

B. BEFORE ANCHORING IN PLACE OPEN AND CLOSE DOOR. CHECK TO SEE THAT THE DOOR IN THE CLOSED POSITION RESTS ON THE FRAME ALL AROUND. IF NOT, SHIM UNDER THE FRAME AT THE PROPER CORNER.

CUSTOMER:

P.O. NO:

JOB:

TAG:

SALES REP:

APPROVED BY:

DATE:

Manufacturers of Doors for Special Services
THE BILCO COMPANY
New Haven, Connecticut 06505

DOUBLE LEAF ACCESS DOOR
TYPE QD - INTERIOR

QTY	TYPE	SIZE WIDTH x LENGTH
☐	QD-1	4'-0" x 2'-6" [1220mm] x [762mm]
☐	QD	____ x ____ HINGE SIDE

FOR SIZE LIMITATIONS ON THIS UNIT, CONSULT FACTORY

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.

© 11-26-25 THE BILCO COMPANY