## SUBMITTAL: EXTERIOR ACCESS PANEL XPA™ and XPS™ SERIES

## PAGE 1 of 2

#### STEP 1 SELECT MODEL:

Model	XPA -	R value	5.7

Frame: 16 ga. galvanneal steel.

Door: 2" Thick with fiberglass insulation, .040 aluminum door with continuous stainless hinge.

Gaskets: Adhesive backed EPDM foam and silicone rubber seals on frame and door.

Finish: White powder coat paint.

Handle: (H2) Non-locking, plastic with chrome finish.

#### \_ Model XPS Stainless steel - R value 5.7

Frame: 16 ga. Stainless steel.

Door: 2" Thick with fiberglass insulation, 20 ga. stainless steel door with continuous stainless hinge.

Gaskets: Adhesive backed EPDM foam and silicone rubber seals on frame and door.

Finish: 304 Stainless - No. 4 finish

Handles: (H2) Non-locking, plastic with chrome finish.

#### STEP 2 SELECT SIZE FROM TABLE BELOW OR ENTER OTHER SIZE:

Sizes: ORDER SIZE IS FRAME ID. Minimum 8" x 8", maximum size 48" x 48"

\_\_\_\_ Other Size \_\_\_\_ W x \_\_\_\_ H

#### STEP 3 SELECT OPTIONAL FEATURES AT ADDITIONAL COST:

\_\_\_\_ (H3) Locking, plastic with chrome finish

\_\_\_\_ (H4) Removable flush locking handle

\_\_\_\_ Rainhood (-R)

\_\_ Optional Color Code - See colors below





**XPS** 

XPA

## Order Format Example: XPA-1212H2W

XP -\_\_\_ -\_\_

XPS Width Height Lock (H2 std) Color Other Options

W (White) B (Bronze) R (Red) BK (Black) S (Sand) AB (AMS Beige) SB (SC Beige) G (Gray) SI (Silver)

QTY	Size (A)	Wall Opening	Handles	Approx Ship Weight in lbs.	QTY	Size (A)	Wall Opening (C)	Handles	Approx Ship Weight in lbs.
	12" x 12"	12-3/8" x 12-3/8"	1	11		24" x 30"	24-3/8" x 30-3/8"	2	40
	14" x 14"	14-3/8" x 14-3/8"	1	15		24" x 36"	24-3/8" x 36-3/8"	2	42
	18" x 18"	18-3/8" x 18-3/8"	1	19		24" x 48"	24-3/8" x 48-3/8"	2	57
	20" x 24"	20-3/8" x 24-3/8"	1	30		30" x 30"	30-3/8" x 30-3/8"	2	44
	20" x 30"	20-3/8" x 30-3/8"	2	32		30" x 36"	30-3/8" x 36-3/8"	2	56
	22" x 30"	22-3/8" x 30-3/8"	2	34		36" x 36"	36-3/8" x 36-3/8"	2	61
	22" x 36"	22-3/8" x 36-3/8"	2	40		36" x 48"	36-3/8" x 48-3/8"	2	75
	24" x 24"	24-3/8"x 24-3/8"	1	27		48" x 48"	48-3/8" x 48-3/8"	2	108

# ACTIVAR CONSTRUCTION PRODUCTS GROUP INC.

800-554-6077

sales@activarcpg.com



www.activarcpg.com

Headquarters: 9702 Newton Ave S. Bloomington, MN 55431

Manufacturing: Minnesota & California Warehouses: See website for locations

### DOWNLOAD CURRENT SUBMITTAL BEFORE ORDERING

[a	
Distributor:	Quantity:
Contractor:	Approved By:
Model #:	Architect:
Project:	Date:

© 2020 Activar Construction Products Group, Inc. | XPATM and XPSTM are trademarks of ACPG.

10/16/2020

# SUBMITTAL: EXTERIOR ACCESS PANEL XP™ and XPS™ SERIES

## PAGE 2 of 2



Typical Wallboard Installation

Gaskets Insulation

Insulation

Stainless Hinge

Dim A + 2"

Typical Masonry Installation

Typical Masonry Installation

### **LATCH AND LOCK OPTIONS**



H2 Non-Locking Handle (Standard)



H3 Locking Handle









Inside Latch for (H4) Removable Flush Locking Handle