# **EXTERIOR: STEEL AND STAINLESS**



## WEATHER-RESISTANT R13 ACCESS PANEL: XT™ SERIES

Select this new exterior access panel design with energy efficiency in mind. 2 inches of polyisocyanurate provides an R-value of 13, and EPDM gasketing provides the weather-resistance you need in sizes up to  $48^{\circ}$  x  $48^{\circ}$ .

#### **XTA: Galvanized & Aluminum Flush Access Panel**

Frame: 16 ga. Galvannealed Steel Frame

Door: 2" Thick Polyisocyanurate Insulation, .040 Aluminum Door Panel.

Finish: White powder coat paint.

#### **XTS Stainless Flush Access Panel**

Frame: 16 ga. Galvannealed Steel Frame

Door: 2" Thick Polyisocyanurate Insulation, 20 ga. Stainless Steel Door Panel


Finish: 304 Stainless – No. 4 Finish

#### **Options:**

(F6) Chrome Lockable Compression Paddle Latch, Optional Colors for XTA



XTS WITH OPTIONAL CHROME LATCH



**XTA** 

# WEATHER-RESISTANT R5.7 ACCESS PANEL XP™ SERIES

This cost-effective solution for providing access to building components features an insulated and gasketed door with interior and exterior handles. Available in a galvanized/aluminum or stainless construction for flush or plaster installation up to 48" x 48".

### **XPA or XPEA: Galvanized & Aluminum Flush Access Panel**

XPA Frame: 16 Gauge Galvannealed Steel Frame with 1" Flange.

XPEA Frame: 16 ga. Galvanneal Steel Frame with Plaster Flange Recessed 3/4";

2-3/4" wide

Door: 2" Thick Insulated .040 Aluminum Door

Finish: White powder coat paint.

### **XPS: Stainless Steel Flush Access Panel**

XPS: Frame: 16 Gauge Stainless Steel Frame with 1" Flange.

XPES Frame: Frame: 16 ga. Stainless Steel Frame with Plaster Flange Recessed

3/4"; 2-3/4"wide

Door: 2" Thick Insulated 20 Gauge Stainless Steel Door

Finish: #304 Stainless – #4 Finish.

**All Models Include:** Continuous Stainless Hinges, EPDM Foam Rubber Bulb Seal and Non-Locking Compression Chrome Plated Handles (H2).


**Options:** Chrome-plated Locking Handle (H3), Removable Flush Locking Handle (H4), Paint Colors, Rainhood.



**MODEL XPA** 







Door Sizes and Wall Openings: Models XTA, XTS, XPA, XPS, XPEA, AND XPES							
A - Order Size = Door Size W x H	C-Wall Opening W x H	Number of Handles	Approximate Shipping Weight	A - Order Size = Door Size W x H	C-Wall Opening W x H	Number of Handles	Approximate Shipping Weight
12" x 12"	12 3/8" x 12 3/8"	1	11 lbs.	24" x 30"	24 3/8" x 30 3/8"	2	40 lbs.
14" x 14"	14 3/8" x 14 3/8"	1	15 lbs.	24" x 36"	24 3/8" x 36 3/8"	2	42 lbs.
18" x 18"	18 3/8" x 18 3/8"	1	19 lbs.	24" x 48"	24 3/8" x 48 3/8"	2	57 lbs.
20" x 24"	20 3/8" x 24 3/8"	1	30 lbs.	30" x 30"	30 3/8" x 30 3/8"	2	44 lbs.
20" x 30"	20 3/8" x 30 3/8"	2	32 lbs.	30" x 36"	30 3/8" x 36 3/8"	2	56 lbs.
22" x 30"	22 3/8" x 30 3/8"	2	34 lbs.	36" x 36"	36 3/8" x 36 3/8"	2	61 lbs.
22" x 36"	22 3/8" x 36 3/8"	2	40 lbs.	36" x 48"	36 3/8" x 48 3/8"	2	75 lbs.
24" x 24"	24 3/8" x 24 3/8"	1	27 lbs.	48" x 48"	48 3/8" x 48 3/8"	2	108 lbs.
Custom Sizes Available Upon Request							

Examples of Optional Colors at Additional Cost - Painted Samples Available

Bronze R-Red BK-Black/FBFIat S-Sand AB-AMS Beige SB-Flat Beige G-Gray SI-Silver